



Alto-Pozz™

Alto-Pozz™ Alto-Pozz is a premium blend of highly reactive pozzolans and mineral admixtures containing 50% post-consumer recycled content. Designed to produce a superior high performance concrete when combined with cement.

Benefits of using Alto-Pozz:

- Reduces concrete permeability
- Decreases efflorescence & controls ASR (Alkali Silica Reaction)
- Improves strength and density
- Improves mix rheology, color & appearance
- Reduces drying shrinkage
- white to off-white in color
- Increases density/tightness of concrete
- Improves surface characteristics

Alto-Pozz™ in your mix:

- Recommended dose is 15-25% cement replacement by weight. Can be dosed up to 30%.

Physical Data:

- Specific Gravity 2.6
- Appearance Off-White, free flowing powder
- Bulk Density (lbs/ft³) 27-35
- Conforms to ASTM C-618 specifications for natural and calcined pozzolans

Storage & Shelf Life:

- Should be stored in in a cool & dry environment. Avoid High humidity which may cause product to clump
- With proper storage conditions the normal shelf life will typically be 12 months

Safe Handling:

- **Alto-Pozz™** is a powder and can create dust. Avoid excessive dust buildup. Keep away from ignition sources. Avoid breathing dust and wear OSHA appropriate dust mask

Limited Warranty:

- This product is warranted to be of merchantable quality when used according to the instruction herein. It is not warranted to be suitable for any purpose or use other than the general purpose for which it is intended. Liability under this warranty is limited to the replacement of the product as purchased, if found to be defective upon inspection by the manufacturer. This limited warranty is issued and accepted in lieu of all other expressed warranties and explicitly excludes liability for consequential damages. Buyer assumes all risk and liability resulting from the use of this product.